

APPARATUS AND METHOD FOR CYCLIC ADJUSTMENT OF A SUPPORTING ELEMENT IN A SEAT

Cross-Reference to Related Applications

None.

10 Statement Regarding Federally Sponsored Research or Development.

Not Applicable.

Background of the Invention

Field of the Invention

15 The present invention relates to an apparatus and method for reducing the symptoms and occurrences of muscle fatigue in a seat occupant and, more particularly, to an apparatus and method for adjusting the position of a supporting element in a seat such as a lumbar support.

Related Art

20 Persons who have to remain seated for relatively long periods of time develop symptoms of fatigue and disturbed circulation, which as a whole have a negative effect on their well-being, concentration, and performance. In the case of relatively long automobile trips in particular, this is undesirable in terms of road safety. In fact it is recommended that people take rest breaks and engage in physical exercises every now and then, but this cannot always be done.

25 Contributing factors to muscle fatigue in sedentary individuals include decreased blood flow and oxygen, individual muscle fiber fatigue, vertebral disk compression and, possibly the build-up of lactic acid within the muscle fibers and surrounding tissues. Additionally, an individual's posture gradually slumps during prolonged periods of sitting thereby changing the

5 curvature of the person's spine. The prior art has recognized that some relief from back pain is provided by manipulating the curvature of a seat occupant's spine. Recent ergonomic studies attribute these problems to static muscle activity, however, which is not relieved by a static lumbar support, even with a customizable curvature. In this regard, the present invention provides for repeated movement of the spinal area and muscle tissues in small increments to
10 create a pumping action that increases blood circulation through the muscle fibers, creates passive movement and prevents lactic acid build-up. The periodic displacement of the spine and muscle tissues by small movements of a lumbar supporting element have been found to be particularly effective at reducing muscle fatigue during prolonged periods of sitting.

As indicated above, there are many seats familiar to the art that attempt to address the
15 occurrence of, and symptoms related to, muscle fatigue and disturbed circulation. More particularly, with respect to motor-vehicle seats, massaging elements, hand-driven or motor-driven arching elements adjustable in height and degree of curvature have been found to be popular with seat occupants for improving posture and comfort. More particularly, the vibrating or massaging mechanisms known in the art directed to relieving the muscle fatigue
20 perceived by the seat occupant also increase blood flow, passively move the spine and mitigate the lactic acid build up. Whether such motion is perceptible to the seat occupant or not depends on many variables. Early studies, such as those cited in U.S. Patent numbers 5,816,653 and 6,007,151 indicated that movement of 6 to 10 millimeters may not be perceptible. More recent studies indicate that many people can feel a movement of such
25 magnitude, although a 12 millimeter move is more readily perceived. More importantly, recent studies reveal that the motion is beneficial whether perceived or not, and that the benefits remain if the motion is a desired comfortable massaging motion.

5 The adjustable arching supporting elements known in the art are generally mechanical or motor driven apparatuses positionable according to the preference of the seat occupant. Such manually actuated systems fail to provide the repetitive and specifically controlled positioning features of the present invention that have been found to be particularly effective at reducing or eliminating lactic acid build-up and muscle fatigue. Prior lumbar support cycling
10 devices such as those disclosed in U.S. Patent number 5,816,653 and U.S. Patent number 6,007,151 necessarily rely on incremental steps understood to be imperceptible. There remains a need for combining the benefits of passive movement with the desirable perceptible movement in an economical, robust device.

Proprietary electromyography ergonomic studies reveal an advantageous decrease in
15 muscle activity with the combined massage effect and cyclic passive motion afforded by a cyclic flexion of variable curvature ergonomic support devices such as a lumbar supports, especially as applied to traction actuated, archable lumbar supports.

SUMMARY OF THE INVENTION

20 In view of the above, the present invention provides an apparatus and method for adjusting the position of a supporting element within a seat according to a specific cycle to relieve muscle fatigue of the seat occupant. The present invention provides a supporting element and drive assembly having a controller adapted to selectively position the supporting element according to a predetermined sequence. The present invention provides a drive
25 assembly having a controller that periodically and repeatedly displaces the supporting element. The present invention provides a method for adjusting the position of a supporting element in a seat in the manner described above.

5 The present invention provides a supporting element within a vehicle seat that includes a controller for automatically adjusting the position of the supporting element according to a predetermined cycle. More particularly, the apparatus of the present invention is adapted for stimulating the muscles of the seat occupant and includes a flexible supporting element adapted to be coupled to a seat for movement relative thereto. A driver automatically and
10 repeatedly moves the flexible supporting element through an adjustment cycle that includes a movement in a first direction to a set position followed by a movement in a second direction to another set position. Each movement is continuous in time, and separated by a pause before direction changes.

 The method of the present invention relieves muscle fatigue in a seat occupant by
15 adjusting the curvature of the supporting element and generally includes the step of placing a supporting element in a first position operatively engaging a muscle of the seat occupant wherein the first position defines a first degree of curvature of the supporting element. The method includes the additional steps of automatically adjusting the curvature of the supporting element according to an adjustment cycle that includes starting at the first degree of curvature,
20 increasing or decreasing the degree of curvature a first amount to define a second degree of curvature, reversing movement direction from the second degree of curvature, and increasing or decreasing the degree of curvature of the supporting element a second amount to define a third degree of curvature.

 A method and data structure are disclosed and claimed for a control system to achieve
25 the cyclic motion pattern. These may be applied to other types of ergonomic supports, such as inflatable bladders, push paddles and flexible wire mat supports.

5 Further features and advantages of the present invention, as well as the structure and operation of various embodiments of the present invention, are described in detail below with reference to the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

10 FIG. 1 is a front view of a supporting element and positioning assembly according to the present invention.

FIG. 2 is a side view of the supporting element shown in Fig. 1.

15 FIG. 3 is a schematic illustration of a positioning assembly control module according to the present invention.

FIG. 4 is a schematic illustration of the position assembly control module according to another embodiment of the present invention.

20 FIG. 5 is a flow chart of the control system and data structure of the present invention.

DETAILED DESCRIPTION

25 The present invention relates to an apparatus and method for adjusting the position of a supporting element in a seat according to a predetermined sequence. In general, the adjustment of the supporting element is controlled by a module that conveys an electric current to an electric motor in a predetermined cycle to automatically and cyclically adjust the position of the supporting element. The periodic adjustment provided by the present invention operates to reduce the muscle fatigue that generally occurs during extended
30 stationary periods in a seat and increases comfort. Additionally, the present invention may impart a desirable massage effect.

The following description of the present invention is merely exemplary in nature and is not intended to limit the scope of the claimed invention. Moreover, while the invention is depicted for use in the lumbar region of a seat, the description is intended to adequately teach

5 one skilled in the art to make and use the apparatus and method described and claimed herein
in a variety of environments. The depicted alternative is a lumbar support of the traction
driven, arching support element type.

As illustrated in FIG. 1 of the drawings, a lumbar support 10 is shown to include a
flexible elastic supporting element having a body 14 interconnecting an upper portion 16 and a
10 lower portion 18. A positioning assembly 20 is coupled to supporting element 12 to selectively
displace upper portion 16 relative to lower portion 18 thereby bowing body 14 such as is
illustrated in FIG. 2. In the preferred embodiment, positioning assembly 20 includes an
electric motor 22 coupled to drive an actuating assembly 24 that includes a cable 25 coupled to
upper and lower portions 16 and 18 of supporting element 12 such as by attachment fitting 26
15 and 28, respectively. While the embodiment of the present invention described herein is
specifically adapted for use with the two-way or four-way electric lumbar supports
manufactured by Schukra of North America Ltd. having a place of business in Windsor,
Ontario, those skilled in the art will appreciate that a variety of supporting elements and
actuating apparatuses may be used with the present invention without departing from the
20 proper scope of the appended claims. For example, the supporting element may include an
inflatable membrane coupled to a pressure regulator, a push paddle, a levered panel or a flexible
wire mat.

Supporting element 12 is illustrated in FIG. 2 to be positionable in a variety of degrees
of curvature of body 14 each defining an apex 27. As described below, apex 27 is displaceable
25 in a first direction indicated by arrow 30 toward the seat occupant and in a second direction
away from the seat occupant and opposite arrow 30 by selectively increasing and decreasing,
the curvature of body 14.

5 FIG. 3 schematically illustrates an embodiment of the present invention wherein
positioning assembly 20 is adapted to change the curvature of supporting element 12 according
to a predetermined adjustment cycle. In this embodiment, positioning assembly 20
interconnects supporting element 12 and a power source 32. As shown, positioning assembly
20 includes a coupling 34, such as the previously described actuating assembly 24,
10 mechanically connecting motor 22 to supporting element 12 and a control module 36
electrically connecting motor 22 to power source 32. As is explained in greater detail
hereinafter, module 36 is adapted to control current to motor 22 in order to selectively drive
motor 22 and displace supporting element 12 according to the predetermined adjustment
cycle. Module 36 embodies the data structure and control system of the present invention.
15 The following description of the components and operation of module 36 provides a general
illustration of the function and operation of the module. However, those skilled in the art will
appreciate that a variety of equivalent components known in the art may be substituted for
those described below and/or the interrelationship between the components may be modified
such that module 36 communicates the same or an equivalent current cycling control of the
20 motor 22.

With continued reference to FIG. 3, an embodiment of controller module 36 is shown
to include an activator 38, current regulator 40, and polarity switch 42 disposed between power
source 32 and motor 22. Activator 38 is illustrated as a switch positionable between an open
position preventing the flow of an electric current from power source 32 to current regulator 40
25 and a closed position wherein an electric current is communicated to current regulator 40. In
the preferred embodiment, activator 38 communicates with an input 39 (FIG. 4) with which a

5 seat occupant can selectively initiate and terminate the performance of the predetermined adjustment cycle.

Cycling begins at a first position of the supporting element selected by a seat occupant by using a separate control such as an electrical switch or mechanical lever. Cycling oscillates between a second position and third position each of which are equidistant from the first position. One of the second and third positions is forward of the first position and the other is rearward of the first position. Preferably, the second position is six millimeters from the first position, and the third position is six millimeters from the first position in the opposite direction, for a total range of travel of 12 millimeters. Ergonomic studies have revealed that this configuration is preferred by surveyed seat occupants. Accordingly, the movement pattern embodied in the data structure and control system of the present invention is understood to represent an optimization of combining the insensate action of passive movement of paraspinal muscles and the spine with the sensation of a massaging action enjoyed by surveyed seat occupants. Other ranges of motion are considered to be within the scope of the present invention, including ranges small enough to be imperceptible to a seat occupant, and ranges large enough to be felt as desirable massaging actions.

In the preferred embodiment, input 39 includes a lumbar switch (not shown) coupled to the exterior surface of the seat. The lumbar switch may be manipulated by the seat occupant to adjust the position of the lumbar support by changing the curvature of supporting element 12. In a manner known in the art, input 39 and activator 38 are configured such that rapid actuation of the lumbar switch initiates the adjustment cycle provided by current regulator 40 by closing activator 38 as described above. Those skilled in the art will appreciate that a variety of equivalent activating structures such as, for example, a momentary switch may be

5 used without departing from the scope of the present invention as defined by the appended claims.

Current regulator 40 functions to selectively communicate an electric current to polarity switch 42 such as by a timing circuit. While activator 38 is in its closed position, current regulator 40 prevents the flow of an electric current to polarity switch 42 during a first
10 time interval and communicates a current to switch 42 during a second time interval. The transition between forward and rearward movements is controlled by polarity switch 42 and switch controller 68.

Polarity switch 42 is of a type generally known in the art and is adapted to selectively reverse the polarity of the electric connection between module 36 and motor 22 so as to cycle
15 the movement of motor 22 in first and second directions. As schematically illustrated in another embodiment of controller module 36 shown in FIG. 4, polarity switch 42 communicates with a switch controller, 78. Switch controller 78 selectively moves polarity switch 42 from and to a first position defining a first polarity connection between module 36 and motor 22 and moves polarity switch 42 to and from a second position defining a second
20 polarity connection. As generally described above, the current regulator 40 communicates to motor 22 through the first polarity connection to define the first movement in the first direction. Similarly, the second polarity connection communicates the second movement in the second direction to motor 22. Motor 22 is coupled to module 36 such that current controlled by the system of the present invention drives motor 22 in a first direction and,
25 through mechanical coupling 34, moves supporting element 12 in the direction indicated by arrow 30. Periodically thereafter, the system of the present invention embodied in module 36 causes motor 22 to move apex 27 of supporting element 12 in the direction opposite arrow 30.

5 It should be appreciated that a variety of electro-mechanical or software implemented polarity switches known in the art may be used with the present invention without departing from the proper scope of the appended claims.

Current regulator 40 is configured to communicate an electric current to polarity switch 42 while the support element 12 moves through a range of positions, to prevent the
10 flow of current during time intervals between movements. The duration of each movement ranges from about 5 seconds to about 25 seconds. The preferred time intervals or pauses are about three (3) seconds.

Those skilled in the art will appreciate that the specific curvature adjustment is dependent upon several variables including the specific configuration of motor 22, the firmness
15 of the supporting element, the amount of padding between the supporting element and the seat occupant, and the load that the seat occupant exerts on the supporting element. With these variables in mind, the preferred curvature adjustment magnitude for the supporting element is one that is sufficient to stimulate the seat occupant's muscles proximate to the supporting element or slightly modify the posture of the seat occupant. A first magnitude of curvature is
20 selected by the passenger with separate controls. The speed of movement is also dependent in application on the variables discussed above.

It should be appreciated that it is possible to specifically control not only the magnitude and frequency of each supporting element curvature adjustment but also the full range of travel of supporting element 12 that is provided by module 36. More particularly, while again being
25 dependent upon variables such as the firmness of the supporting element and the amount of padding between the supporting element and the seat occupant, the full range of apex travel in known lumbar supports is up to fifty (50) millimeters.

5 It is specifically preferred that the magnitude of each movement of apex 27, be within the range of about twelve (12) millimeters. This periodic movement of the occupant's muscles and spine is generally sufficient to increase circulation and decrease muscle fatigue that generally occurs during periods of sitting.

Switch controller 68 (FIG. 3) is adapted to change the position of switch 42 at
10 predetermined displacement magnitudes or time periods thereby reversing the polarity of the connection between module 36 and motor 22. For example, it is preferred that module 36 includes end stops (not shown) defining the maximum and minimum curvature displacement provided by the adjustment cycle. Among the many options familiar to the art, end stops may include mechanical stops preventing movement of the motor or actuator beyond the maximum
15 or minimum values, software implemented stops of a similar nature, or a counter for limiting the time period for generating current through a particular polarity. Of course, other equivalent timing or measurement apparatuses may be used without departing from the scope of the invention as defined by the appended claims. The preferred end stop configuration is described more fully below.

20 Those skilled in the art will appreciate that activator 38 is adapted to remain in the closed position allowing current regulator 40 and polarity switch 42 to continually generate and communicate current to motor 22 until the operator cancels the adjustment cycle. It is contemplated that cancellation may occur through manual or automatic intervention. For example, in the preferred embodiment, manual actuation of the lumbar switch via input 39
25 operates to open activator 38 thereby terminating the adjustment cycle. Similarly, the adjustment cycle may be cancelled after a fixed time period, for example ten minutes, when the vehicle ignition is turned off, or any other manner known in the art. Readjusting the initial,

5 central, first curvature position of the support element also stops the cycling movements. It should be appreciated that the adjustment cycle may be reinitiated at any time by the seat occupant such as through input 39 in the manner previously described.

10 In addition to the automated supporting element adjustment feature, the embodiment of controller module 36 shown in FIG. 4 includes a position indicator 74 communicating with motor 22 and a memory 76. In a manner generally known in the art, position indicator 74 is adapted to record the position of motor 22, actuator 24, or support element 12 in a register of memory 76 upon initiation of the adjustment cycle through activator 38 and input 39. In this embodiment, module 36 includes a controller 78 adapted to retrieve the initial position from memory 76 and return motor 22, actuator 24, or supporting element 12 to the initial position upon cancellation of the adjustment cycle. Accordingly, controller 78 is shown to communicate with power source 32, polarity switch 42, and memory 76 such that controller 78 may selectively position polarity switch 42 and communicate an electric current of an appropriate duration to return the motor 22 or other element to the initial position. Those skilled in the art will appreciate that a variety of position indicating structures known in the art may be used with the present invention, such as, for example, a transducer, without departing from the scope of the appended claims.

15 As described above, the present invention provides an apparatus and method for adjusting the position of a supporting element within a seat according to a predetermined cycle in order to relieve muscle fatigue of the seat occupant. The repeated movement of the supporting element creates a pumping action that increases blood circulation through the muscle fibers and prevents lactic acid build-up within the muscles. Passive motion of spine and muscles reduces or eliminates muscle fatigue that generally occurs during long periods of

5 sitting. While the preferred timing of the supporting element adjustments described and claimed herein have been found to be particularly suitable for relieving muscle fatigue in the present apparatus and method, those skilled in the art will appreciate that other time intervals and adjustment magnitudes may be used without departing from the proper scope of the present invention as defined by the appended claims.

10 Figure 5 is a flow chart of the control system of the present invention, as embodied in controller module 36, current regulator 40 and controller 78. The data structure represented by Figure 5 is stored in a machine readable format, preferably a transistor configured integrated chip and most preferably a MC68HC705B16, which is a Motorola 8-bit micro-controller.

15 Establishing steps 80 and 82 are executed manually by a seat occupant. The passenger adjusts, 80, the position of the supporting element 12 to a desired, comfortable position, which becomes the first position of the cycle. The first position is also the center of the cycle range, except in cases where the range would extend beyond the mechanical limits of the supporting element, which is managed by the control system in a manner more fully set out below. If the position is not comfortable, the passenger re-adjusts it, 82. This final setting before cycling
20 initiates the control system to establish the relative positions at which inward movement will stop and outward movement begin and visa versa, which position information is monitored by position sensor 74. Position sensing is a well known art and various sensors which may be placed in various places on the unit are known, and known to be equivalent alternatives.

25 After the desired first position is set, the passenger presses a separate button to initiate cycling, 84. The control system signals the motor to begin a first movement, 86, in a first direction, which is inwards in figure 5. Equivalently, the first movement could be outwards. The control system monitors the position of the support element 12 by checking the position

5 sensor 74. When a check of the position sensor first indicates that a second, innermost position six millimeters from the first position has been reached, 88, the next step of the control system, 90 is executed. Before that second position is reached, current flow to the motor 22 is maintained according to step 86 so that the support element keeps moving. The second position is known from step 82, where the first position was selected, initializing a
10 position representation in a memory register of the control system for all three relevant positions.

Upon reaching the innermost (or alternatively, outermost) second position six millimeters from the first position motion is stopped, 88. A timer is initiated to wait three seconds, 90. This pause to maintain a set curvature of spine and muscles corresponds to
15 ergonomic study results indicating the desired and beneficial cycle parameters.

At the end of the three second pause, the polarity switch 42 is reversed and current re-initiated to motor 22 in order to start a second movement in a second direction, 92. Again the position sensor monitors the movement of the support element 12 to determine if the position of it has yet matched the third position which was initialized in step 82. The control system
20 continues current to the motor 22 in the second direction until the support element 12 has moved 12 millimeters in that direction, 94. When 12 millimeters has been traveled and the third position reached, current is again interrupted and the timer again engaged to pause movement.

When the second pause is finished, the polarity switch 42 is again reversed, current
25 flow again re-initiated with the reversed polarity and another movement in the first direction begun, 98. Since this movement begins at the third position, which is at the full extent of the preconfigured cycle range, instead of beginning at the first, central position, the third

5 movement in the first direction must go 12 millimeters to reach the second position, which is
at the other full extent of the preconfigured cycle. Accordingly, the control system has the
third monitoring loop, 100, for monitoring the continuing 12 millimeter back and forth
movements. Only the first movement is 6 millimeters. An option not depicted in Figure 5 is
a final 6 millimeter move to return the support element 12 to the original, first position after
10 cycling stops.

Cycling is stopped by any one of at least three events. One is the passenger readjusting
the first initial position again, as she did at step 80. Using that control during cycling stops
the cycling, 104, and re-initiates the control system memory register with new first, second
and third position values. Turning off the automobile also stops cycling.

15 Finally, the cycle is preconfigured to automatically stop after ten minutes. The control
system checks a timer at 102. If ten minutes is not up, the cycle is continued at step 90 so
that 12 millimeter moves continue. If ten minutes has been reached, the control system stops
the cycle.

It is considered to be within the scope of the present invention that it may be used to
20 control cycling movement of any type of ergonomic support for automobile seats, furniture and
the like. The depicted alternative embodiment is an automobile seat using a lumbar support of
the traction actuated, arching support element type depicted in Figures 1 and 2. It is
considered to be within the scope of the present invention that it may be used to control
cycling movement of any type of lumbar support, including push paddles, flexing wire mats,
25 bladders and the like.

The traction actuated, arching support element type of the depicted alternative
embodiment typically has a total, mechanical range of about 40-50 millimeters. If, for

5 example, a lumbar support with a 50 millimeter range is used, the passenger can set the first position anywhere from 6 millimeters to 44 millimeters and cycling will proceed as described above. In the following manner, the control system of the present invention can also cycle through a truncated range in the case of a first position setting between zero and six millimeters and 44 and 50 millimeters, where the normal cycle range would be interrupted by
10 the mechanical limits of the support element 12.

Stall sensors, 70, and their installation and use are known to those of skill in the art. Generally, they are simple ampmeters set to send a signal when a motor's amperage exceeds a preconfigured limit, as in the case of a motor mechanically prevented from further turning, as would be the case at the ends of the total range of the depicted lumbar support. Other types of
15 stall sensors or position sensors indicating the ends of the total range of the depicted lumbar support could be used within the scope of the present invention, such as, for example, software implemented end stops.

In the preferred end stop configuration, switch controller 68 includes a stall sensor 70 configured to detect the stalling of motor 22 upon reaching one of the respective mechanical
20 end stops. In the preferred embodiment, stall sensor 70 is a current meter communicating with polarity switch 42 and adapted to actuate switch 42 when the measured current exceeds a predetermined value. It is contemplated that the specifications of motor 22 provide for a running current between 0.7 and 3.0 amperes with an optimal running current of 1.25 amps. In this configuration the stall current of motor 22 is 6.5 to 7.0 amperes. The full travel of the
25 motor 22, actuator 24, or supporting element 12 to their mechanical limits is used as the end stops.

5 The control system of the present invention incorporates stall sensor feedback at steps 106, 108 and 110. When the mechanical end of the support element 12 range stalls the motor 22, current is stopped and movement in that direction is curtailed. As indicated in figure 5, when this happens, the three second pause step is immediately begun, and cycling continues from there with a succeeding movement in the opposite direction. This may happen on every 10 cycle when the movement proceeds to a stall, resulting in a continuing cycle that is truncated by the end of the support element range. Travel in the opposite direction would continue to the full extent of the six millimeters from the first position. For example, if the first position was selected at 48 millimeters on a 50 millimeter range lumbar support, inward movement would proceed normally to the 42 millimeter position, but outward movement would be 15 limited to two millimeters by the stall turn at the 50 millimeter limit. The total cycle range would be eight millimeters.

 The passenger can set only the first position of the support element, 12. While the order of movements, range of movement, duration of the cycling and length or existence of pauses may not be altered by the passenger in the depicted alternative embodiment, other 20 embodiments wherein the passenger can control these parameters are considered to be within the scope of the present invention. Likewise, alternate preconfigurations of these parameters by the manufacturer, assembler or ultimate seller of the device or seats incorporating it are also considered to be within the scope of the present invention.

 In view of the foregoing, it will be seen that the several advantages of the invention are 25 achieved and attained.

 The embodiments were chosen and described in order to best explain the principles of the invention and its practical application to thereby enable others skilled in the art to best

5 utilize the invention and various embodiments and with various modifications as are suited to
the particular use contemplated.

As various modifications could be made in the constructions and method herein
described and illustrated without departing from the scope of the invention, it is intended that
all matter contained in the foregoing description or shown in the accompanying drawings shall
10 be interpreted as illustrative rather than limiting. Thus, the breadth and scope of the present
invention should not be limited by any of the above-described exemplary embodiments, but
should be defined only in accordance with the following claims appended hereto and their
equivalents.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
221